

XCNTPERCHAP

**Store counter values per chapter (or other track
levels)**

Documentation

Version 0.4

04/30/2017

Autor: Christian Hupfer[†]








[†]typography.with.latex@gmail.com

Contents





1 Disclaimer	4
2 Introduction	4
3 Package options	4
4 Requirements and incompatibilities	4
4.1 Required packages	4
4.2 Incompatibilities	5
5 Documentation of Macros	6
5.1 Preamble only commands	6
6 User commands	6
7 Experimental features	7
8 Examples	8
8.1 Item count of enumerate	8
8.2 Item count of enumerate – alternate version	10
9 To-Do list	12
10 Acknowledgments	13
11 Version history	13
Index	15


Typographical conventions

Throughout this documentation following symbols and conventions are used:


-  **foo** means a the class `foo`
-  **foo** names a package `foo`
-  **foo** indicates a counter named `foo`
-  `foo` will indicate either a file named `foo` or a file extension `foo`
-  `foo` will indicate some files
-  **foo** names a special feature or tag `foo`
-  **foo** deals with a command or package option named `foo`



1 Disclaimer

This package as of its version 0.4 is a rewrite of the former  **cntperchap** by the same author, is under constant development and as such subject to macro interface changes as well as renaming of macros. Not all features of the previous package has been incorporated so far – if some functionality of your document depends on  **assoccnt**, continue using the older version and shift gradually to  **xcntperchap** please, which uses the newer  **xassoccnt**.

 Most times class and package authors will benefit of this package, but there might be usual documents that need the features of `|xcntperchap|`

2 Introduction

The aim of this package is to provide support for a summary in advance how many sections, subsections, etc. or figures, tables, equations there will be in predefined track level, for example per chapters. The values are stored at the beginning of such a new track level, say `\chapter` and written to a  `jobname.cpc` file.

 Since the  **page** counter is an unreliable 'friend' it is not advised to use this counter as a track level.

As of version 0.4 there is no default version of a track level.

This package is the consequence of the question <http://tex.stackexchange.com/questions/241559/how-to-count-the-total-number-of-sections-within-a-chapter> by the user `gsl`.

3 Package options

As of version 0.4 the package has no package options.

4 Requirements and incompatibilities

4.1 Required packages








Since  **xcntperchap** is written using  **expl3**, it requires the  **xparse** package. It relies on the features of associated counters introduced by  **xassoccnt** v1.4.



-  **zref**
-  **expl3**
-  **xparse**

-  **xassocnt**

The package  **xparse** is already loaded by  **assocnt** and does not need to be specified again.

4.2 Incompatibilities

This package has been tested with the standard classes  **article**,  **book** and  **report** as well as with  **memoir** and the relevant  **KOMA** equivalents. As of version 0.4 for those classes there are no known incompatibilities with the general behaviour of the package, however, there is an issue with  **assocnt** and  **xifthen** which is not solved so far.

It would be nice to adapt the package for usage on a per frame base with the  **beamer** class, but this seems both not really necessary as well as quite difficult, since  **beamer** follows different strategies about the usage of “pages” or “sections”, see 9



5 Documentation of Macros




5.1 Preamble only commands

`\RegisterTrackCounter`{*<track counter>*}{*<counter1, counter2,...>*}

This provides the means to let the package know that the counters should be tracked for values inside a certain track level – specify this in the document preamble.

v0.3 2017-01-09

Description of arguments of command `\RegisterTrackCounter`

- {*<track counter>*} This contains the counter name which is the track level, e.g.  **section**
- {*<counter1, counter2,...>*} This marks the counters to be tracked inside the track level, e.g.  **subsection**,  **subsubsection**

`\RegisterMultipleTrackCounters`{*<track counter 1, track counter 2,...>*}{*<counter1, counter2,...>*}

This provides the means to let the package know that the counters should be tracked for values inside multiple track levels – specify this in the document preamble.

v0.3 2017-01-09

All counters in the 2nd mandatory argument will be tracked by **all** track levels.

Description of arguments of command `\RegisterMultipleTrackCounters`

- {*<track level 1, track level 2,...>*} This list contains the counters which are track levels
- {*<counter1, counter2,...>*} This marks the counters to be tracked inside of each(!) track level.

`\RegisterCounters`{*<track counter>*}{*<counter1, counter2,...>*}

`\RegisterCounters` has the same meaning like `\RegisterTrackCounter` and is the old name for this. Use the newer version for new documents since this command will be removed one day.

v0.1
2016-05-22

6 User commands



`\ObtainTrackedValue`[*<counter value>*]{*<track level>*}{*<tracked counter>*}


This command prints the value of the tracked counter of a track counter, i.e. the number of subsections in a specific chapter, say, the 5th chapter can be obtained by


v0.1
2016-05-22

```
{listings only}
\ObtainTrackedValue[5]{chapter}{subsection}
```

```
listings only
```

- #1 [*options*]: As of version 0.4, the only option is a counter value, say 5 for the 5th chapter. This must be the total number of the relevant track counter, i.e. the 17th total section etc.
- #2 {*track counter name*}: The name of the track level, i.e.  **section**.
- #3 {*tracked counter name*}: The name of the tracked counter, i.e.  **figure**.

Please note that the number of entities per track level might be reported wrongly for floats, since those are shifted to some other places. If this should be prevented, a `\FloatBarrier` from  **placeins** might be necessary (see the example file `xcntperchap_driver.tex`)

 This macro is not expandable – for an expandable version use `\ObtainTrackedValueExp` instead.

v0.2
2016-06-
07

Expandable

v0.2
2016-06-
07


`\ObtainTrackedValueExp` [*counter value*] {*track level*} {*tracked counter*}



This command is the expandable version of `\ObtainTrackedValue`^{→P.6} and should be used if calculations, comparisons and write - operations to files are requested.

The meaning of arguments is the same as in `\ObtainTrackedValue`^{→P.6}.


7 Experimental features

v0.3 2017-
01-09


 The content and description of the features are marked as experimental as of version 0.4. Features are subject to changes as well as macro names might be revised in future versions.

The tracking of counters with respect to some fixed number of a track level counter might get tedious, i.e. it is not very convenient to remember a special section number of which counter  **foo** should be tracked.  **xcntperchap** provides the possibility to add a label to some track level counter and obtaining the running total number of the relevant counter by using `\ObtainTrackedValueByLabel`^{→P.8}.

`\tracklabel` [*counter name*] {*label name*}

`\tracklabel` provides a label given in the first mandatory argument to a track level counter – the counter is being auto detected with `\LastRefSteppedCounter` from  **xassocnt**.

In addition, the a label with the same name is set with the usual `\label` command. Use `\tracklabel*`^{→P.8} to suppress the generation of such labels.

- #1 [*counter name*]: This is only used as an optional argument to the `\label` command as provided by  **cleveref**.

v0.3 2017-
01-09

#2 $\{\langle label name \rangle\}$: A label for a track level counter.

`\tracklabel*[\langle counter name \rangle]\{\langle label name \rangle\}`

This is the starred version of `\tracklabel`^{P.7} but does not generate a usual label of the name given with the first mandatory argument. The optional argument is ignored as of version 0.4.

v0.3 2017-01-09



Please note that the usability of `\tracklabel`^{P.7} is restricted to track level counters that have been used with `\refstepcounter` as of version 0.4!

`\ObtainTrackedValueByLabel[\langle counter name \rangle]\{\langle label name \rangle\}\{\langle tracked counter \rangle\}`

Expandable

This command uses a label given with `\tracklabel`^{P.7} to some track level counter usage and will return the relevant number of the tracked counter. The underlying track level counter is autodetected using [zref](#) properties.

v0.3 2017-01-09

- #1 $[\langle counter name \rangle]$: Use this to override the auto detection of the track level counter. This might cause unpredictable logical errors, however.
- #2 $\{\langle label name \rangle\}$: A label for a track level counter.
- #3 $\{\langle tracked counter \rangle\}$: The name of a counter being in the tracking list of the (auto detected) track level counter.
 - If the given label is not defined, a ?? is printed instead. As of version 0.4 there is no warning or error message.
 - This command is expandable!

See Section 8.2 for an example using the tracking - by - label - feature.

`\AddToTrackedCounters\{\langle tracked counters \rangle\}\{\langle counter value \rangle\}`

This macro adds the same value to a comma separated list of tracked counters without using `\stepcounter`.

v0.3 2017-01-09

- #1 $\{\langle tracked counters \rangle\}$: A comma separated list of counter names.
- #2 $\{\langle counter value \rangle\}$: An integer value

8 Examples

8.1 Count the items of an enumerate

```
\documentclass{article}
```



```

\usepackage{xcntperchap}
\usepackage{enumitem}

\RegisterCounters{section}{enumi}
\RegisterCounters{subsection}{enumi}

\begin{document}
\tableofcontents

\section{Section 1 -- with \ObtainTrackedValueExp{section}{enumi} items}
  \begin{enumerate}[resume]
    \item Item 1
    \item Item 2
    \item Item 3
  \end{enumerate}

\subsection{Another subsection with \ObtainTrackedValueExp{subsection}{enumi} }

\begin{enumerate}[resume]
\item Item 4
\item Item 5
\end{enumerate}

\section{Section 2 -- with \ObtainTrackedValueExp{section}{enumi} items}
\begin{enumerate}[resume]
\item Item 6
\item Item 7
\end{enumerate}

\subsection{Another subsection with \ObtainTrackedValueExp[2]{subsection}{enumi} }
  \begin{enumerate}[resume]
    \item Item 8
    \item Item 9
    \item Item 10
    \item Item 11
    \item Item 12
    \item Item 13
  \end{enumerate}

\end{document}

```

8.2 Count the items of an enumerate – with label reference

```

\documentclass{article}

\usepackage{xcntperchap}
\usepackage{enumitem}

\RegisterCounters{section}{enumi}
\RegisterCounters{subsection}{enumi}

\begin{document}
\tableofcontents

\section{Section 1 -- with \ObtainTrackedValueExp{section}{enumi} items} 2
  {\tracklabel{sectionlabel}
  \begin{enumerate}[resume]
    \item Item 1
    \item Item 2
    \item Item 3
  \end{enumerate}

\subsection{Another subsection with \ObtainTrackedValueExp{subsection}{enumi} items}

\begin{enumerate}[resume]
\item Item 4
\item Item 5
\end{enumerate}

\section{Section 2 -- with \ObtainTrackedValueExp{section}{enumi} items}
\begin{enumerate}[resume]
\item Item 6
\item Item 7
\end{enumerate}

\subsection{Another subsection with \ObtainTrackedValueExp[2]{subsection}{enumi} 2
  {\Items } \tracklabel{subsec::somelabel}


However, you can use a label as well: 2
  {\ObtainTrackedValueByLabel{subsec::somelabel}{enumi} Items

\begin{enumerate}[resume]
\item Item 8
\item Item 9

```

```
\item Item 10  
\item Item 11  
\item Item 12  
\item Item 13  
\end{enumerate}  
  
\end{document}
```

9 To-Do list

- Better error handling (no checks for many features so far).
- More options for fine control of the behaviour package and macros.
- Easy - adaption for other documentclasses, especially for  **beamer**
- Improve documentation
- More examples

If you

- find bugs
- errors in the documentation
- have suggestions
- have feature requests


don't hesitate and contact me via christian.hupfer@yahoo.de

10 Acknowledgments



I would like to express my gratitudes to the developpers of fine \LaTeX packages and of course to the users at tex.stackexchange.com, especially to

- Paulo Roberto Massa Cereda
- Enrico Gregorio
- Joseph Wright
- David Carlisle
- Werner Grundlingh
- Gonzalo Medina

for their invaluable help on many questions on macros.

! A special gratitude goes to Prof. Dr. Dr. Thomas Sturm for providing the wonderful  [tcolorbox](#) package which was used to write this documentation.

11 Version history

- Version v0.4 2017-04-19 Improved the core `\stepcounter` in order to fit the  [expl3](#) and  [xparse](#) changes of Februar - April 2017.
- Version v0.3 2017-01-09
 - Support for obtaining a tracked value level by using labels with `\tracklabel→P.7`, `\tracklabel*→P.8` and `\ObtainTrackedValueByLabel→P.8`
 - Added the `\RegisterTrackCounter→P.6` and `\RegisterMultipleTrackCounters→P.6` as a replacement of `\RegisterCounters→P.6`.
 - Added `\AddToTrackedCounters→P.8` macro to circumvent counter value update problems for specific tracked counters.
- Version v0.2 2016-06-07
 - Added the expandable version of `\ObtainTrackedValues`

v0.3 2017-01-09

v0.3 2017-01-09

v0.2
2016-06-07

- Removed the bug concerning the missing reset of the associated counters

- Version v0.1 2016-05-22

Bootstrap version, rewrite of previous  **cntperchap** with LaTeX - 3 - Kernel features

v0.1

2016-05-

22

Index

`\AddToTrackedCounters`, 8

Counter
 foo, 7

`\ObtainTrackedValue`, 6

`\ObtainTrackedValueByLabel`, 8

`\ObtainTrackedValueExp`, 7

Package

- article, 5
- assoccnt, 4, 5
- beamer, 5, 12
- book, 5
- cleveref, 7
- cntperchap, 4, 14
- expl3, 4, 13
- KOMA, 5
- memoir, 5
- placeins, 7
- report, 5
- tcolorbox, 13
- xassoccnt, 4, 5, 7
- xcntperchap, 4, 7
- xifthen, 5
- xparse, 4, 5, 13
- zref, 4, 8

`\RegisterCounters`, 6

`\RegisterMultipleTrackCounters`, 6

`\RegisterTrackCounter`, 6

`\tracklabel`, 7

`\tracklabel*`, 8